



kappaRACK Installation Instructions

Rev. A

Page 1 of 8

Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

READ FITTING INSTRUCTIONS IN FULL BEFORE INSTALLATION

This article is sold without warranty expressed or implied. No warranty or representation is made as to this products ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the manner in which it is INSTALLED, USED, and/or MAINTAINED. THE USER ASSUMES THE RISK.

By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these Kappasphere products from Kappasphere, its affiliates, distributors, and agents (collectively, Kappasphere) **as is** and **with all faults**.

The entire risk as to the quality and performance of these Kappasphere parts is with the purchasers. Working on your car can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or Safety critical work to a skilled mechanic.

We take no responsibility for the incorrect use and/or installation of Kappasphere products.

Warning! This luggage rack should not hold weights exceeding 50lbs.

Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration



1. Prep.
Car

- Cleaning Supplies

- a. Make sure car is clean and dry before installation of luggage rack.
- b. Add a thick layer of automotive wax or a thin layer of clear bra film on the trunk where the rubber strips will be in contact with the paint to help minimize the chances of the rubber marking or road grime that may get under the rubber stripes and cause scratching.
- c. Open trunk lid and make sure it is clean of all contaminants.



Assembly Step	Tools/ Parts	Detailed Instructions	Picture/ Illustration
---------------	--------------	-----------------------	-----------------------

<p>2. Parts Inventory and tools needed.</p>	<ul style="list-style-type: none"> • 1 Left Front Strap • 1 Right Front Strap • 1 Left Rear Strap • 1 Right Rear Strap • 2 Rubber Strap Protection Strips • 12 Plastic washers • 12 metal washers • 6 Lock nuts • 2 1.25" bolts • 4 1" bolts • Screws • 4 plastic end caps 	<p>Look over all parts to be used. Lay hardware out and account for.</p> <p>Tools needed:</p> <p>2 x 13mm wrench</p> <p>3/4 drive ratchet drive</p> <p>5mm allen socket or key</p> <p>Cloth to protect surface while working.</p>	 
---	--	---	--

Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

3.Assemble

a. Next you want to put the straps together. Both straps consist of four individual pieces. The rear straps are marked “LR” and “RR” and are also angled to conform to the angle on the deck lid.

b. Once you know how they go, add the rubber strap (*Use soapy water or a healthy amount of WD-40 to help slide on the rubber straps*) and the place the plastic strap end caps on the ends of the metal straps.



Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

4.Assemble

a. Refer to Picture:
Note four mount tabs
on bottom of rack



Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

5.Assemble

b. Mount both strap assemblies on to deck lid using center line to center entire assembly. The straps should be 12” apart to mate with rack attachment tabs.

c. Place plastic inserts into ends and starting from the top place the straps over the edge and let hang. Grasp the upper stanchion, pull down enough to secure bottom of strap to bottom of deck lid. Tighten center bolt & nut assembly to pull ends together tightening straps to surface.



Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

6.Assemble

d. Place rack in position and tighten with remaining bolt & nut assemblies. Be sure to install plastic washers between the rack & strap assemblies and bolt, metal washer & nut assemblies before installing and tightening.



Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

7.Assemble

The Kapparack has a new benefit of having the ability to be reversed.

Remove the 4 fastening points. Position rack to desired end.

Tighten.

